



## GL-5 LIMITED SLIP GEAR OIL

Multi-Purpose Automotive/HD Gear Oil  
Full Limited Slip Additive Treatment



Fleet/Farm/Off-Road

REV: 06.08.2017



### DESCRIPTION

Xtreme™ SAE 85W-140 GL-5 Gear Lubricant with limited slip additive is a premium quality extreme pressure (EP) gear oil for manual transmissions and final drives in both automotive and heavy duty applications.

### BENEFITS

- ❑ Excellent thermal and oxidation stability
- ❑ Excellent hydrolytic stability
- ❑ Extreme pressure additives prevent gear scuffing and scoring
- ❑ Excellent resistance to foaming
- ❑ Proper friction control for Limited Slip applications
- ❑ Prevents formation of rust and sludge throughout the system
- ❑ Prevents corrosion of copper and brass

### APPLICATION

- Ideal for automotive and truck manual transmissions and differentials
- Complete or Service Fill for limited slip synchromesh drive trains
- Excellent for off-road construction and agricultural equipment
- For use in heavy duty trucks and buses as a final drive lubricant

### PERFORMANCE

#### Performance Levels

- API - Service Level GL-5, GL-4
- SAE J-2360
- Military Spec - MIL-L-2105D, 2015E
- Mack Truck - GO-G, GO-H

TYPICAL PROPERTIES	METHOD	SAE 85W-140 GL-5
Specific Gravity at 60°F	D-4052	0.908
Viscosity, cSt at 40°C	D-445	380.5
Viscosity, cSt at 100°C	D-445	27.9
Viscosity Index	D-2270	100
Flash Point, COC °C (°F)	D-92	216 (421)
Pour Point, °C (°F)	D-97	-21 (-6)
ML Reference No.		567939



#### NOTE:

The information on this Product Data Sheet is believed to be accurate and is typical of current production. Specifications are subject to change without notice. For additional qualifications, please contact Martin Technical Service Department.

**Health And Safety Information** See separate Safety Data Sheets available on request.

**Xtreme™ and Martin Lubricants™** are trademarks of Martin Lubricants. All other marks are property of their respective owners