



# RIG ROCK DRILL OIL

For Use in the Oilfield Industry



REV: 10.02.2024



## DESCRIPTION

Xtreme Rig Rock Drill Oil is produced from premium base oil selected for its ability to minimize carbon deposits and fortified with tackiness additives to cling to moving equipment components during operation.

Xtreme Rig Rock Drill Oil is recommended for use in the oil field industry to lubricate pump plungers on salt water disposal wells.

## BENEFITS

- Reduced heat
- Low fogging tendencies
- Environmentally friendly ashless formulation

## APPLICATION

- Lubrication of pump plungers in salt water disposal wells
- Other general lubrication applications where tackiness additives are needed

## PERFORMANCE

**Recommended Temperatures** **100**  
 Operating Range, °F, °C 40 to 80 (4 to 27)

TYPICAL PROPERTIES	METHOD	Rig Rock 100
Specific Gravity	D-4052	0.920
Viscosity, cSt at 40°C	D-445	119.2
Viscosity, cSt at 100°C	D-445	10.1
Pour Point, °C (°F)	D-97	-25 (-13)
Flash Point, COC °C (°F)	D-92	198 (388)
ML Reference No.		573360



### NOTE:

The information on this Product Data Sheet is believed to be accurate and is typical of current production. Specifications are subject to change without notice. For additional qualifications, please contact Martin Technical Service Department.

**Health And Safety Information** See separate Safety Data Sheets available on request.

**Xtreme™ and Martin Lubricants™** are trademarks of Martin Lubricants. All other marks are property of their respective owners