



# EXTREME PRESSURE Rock Drill Oil

Blended From Premium Base Oils  
For Use in Pneumatic Equipment



REV: 10.02.2024



## DESCRIPTION

Xtreme™ EP Rock Drill Oils are blended from premium base oils selected for their ability to minimize carbon deposits and fortified with extreme pressure additives, rust and oxidation inhibitors, smoke inhibiting additives and tackiness additives to cling to moving parts of pneumatic percussion tools.

Xtreme™ EP Rock Drill Oils are recommended for use in lubricating all types of pneumatic equipment such as jackhammers, pavement breakers, stoppers, drifters and down home drills in road construction , quarries and mining.

## BENEFITS

- ☑ Protection of metal surfaces against shock loading and boundary lubrication
- ☑ Inhibits rust, corrosion and foaming
- ☑ Reduced heat in pneumatic tools
- ☑ Contains ashless anti-wear additives for maximum protection to moving parts under extreme pressure
- ☑ Low fogging tendencies
- ☑ Environmentally friendly ashless formulation

## APPLICATION

- Pneumatic percussion tools in quarries and road construction and other rock drilling or breaking applications
- Pneumatic tools in a wide variety of applications where EP properties and tack additives are recommended

## PERFORMANCE LEVELS

- Ingersoll-Rand
- Gardner-Denver
- Joy / Sullivan
- Atlas Copco (Chicago Pneumatic)

TYPICAL PROPERTIES	METHOD	ISO 68	ISO 100	ISO 150	ISO 220	ISO 320	ISO 1000
Specific Gravity at 15.6°C	D-1298	0.8747	0.8786	0.8766	0.8872	0.8925	0.9176
Viscosity, cSt at 40°C	D-445	71.9	104.3	145.7	217.1	313.6	925.3
Viscosity, cSt at 100°C	D-445	9.0	11.8	15.5	19.6	24.6	-
Flash Point, COC, °C	D-92	174	200	204	222	231	240
Pour Point, °C	D-97	-35	-21	-18	-15	-12	-11
4-Ball Weld Load, kgf	D-2783	250	250	250	250	250	250
Operating Range, °F(°C)		0-50 (18-10)	40-80 (4-27)	75-100 (24-38)	>75 (24)	>75 (24)	>80 (>27)
ML Reference No.		574055	573440	574063	582354	573466	582856



### NOTE:

The information on this Product Data Sheet is believed to be accurate and is typical of current production. Specifications are subject to change without notice. For additional qualifications, please contact Martin Technical Service Department.

**Health And Safety Information** See separate Safety Data Sheets available on request.

**Xtreme™ and Martin Lubricants™** are trademarks of Martin Lubricants. All other marks are property of their respective owners