



Orchard 60 SPRAY OIL

Dust Suppression Oil
For Use In Agriculture, Roads, And Mining Operations



REV: 10.02.2024



DESCRIPTION

Orchard Spray Oils are blended from premium naphthenic base oils selected for their excellent clarity and color. These oils are non-emulsified for use as a dust control oil. This selection of base oil safely coat dust particles and prevent them from becoming airborne.

BENEFITS

- Low odor and good color stability
- Approved for use in food industry applications

APPLICATION

- AGRICULTURAL
- ROADS
- MINING
- ROADS
- ENERGY

PERFORMANCE

Performance Levels

- ANSF Food Grade H-2 Approved

TYPICAL PROPERTIES	METHOD	Orchard Spray Oil
Specific Gravity at 15.6°C	D-1298	0.9007
Viscosity, cSt at 40°C	D-445	9.9
Viscosity, cSt at 100°C	D-445	2.4
Viscosity Index	D-2270	37
Flash Point, COC °C (°F)	D-92	149 (300)
Pour Point, °C (°F)	D-97	-57 (-71)
Aniline Point, °C (°F)	D-611	67 (153)
Sulfur Content, % wt	D-4294	0.03
ML Reference No.		531047



NOTE:

The information on this Product Data Sheet is believed to be accurate and is typical of current production. Specifications are subject to change without notice. For additional qualifications, please contact Martin Technical Service Department.

Health And Safety Information See separate Safety Data Sheets available on request.

Xtreme™ and Martin Lubricants™ are trademarks of Martin Lubricants. All other marks are property of their respective owners