



XTREME FLUID 334

Construction, Farm, & Logging
Mobile Equipment Fluid



Fleet/Farm/Off-Road

REV: 10.22.2025



DESCRIPTION

Xtreme™ Fluid 334 is designed to be a universal, multi-purpose lubricant for construction, farm, and logging equipment. Manufactured with base oil and additives that provide 3 season performance in spring, summer, and fall in addition to providing 3 layers of protection including anti-wear, rust, and oxidation.

Xtreme Fluid 334 will provide an economical solution in the 4 applications found in common sump systems that contain wet brakes, hydraulics, final drives, and transmissions. This product is ideally suited for equipment that may be aging and requires frequent fluid replacement. Not recommended for equipment manufactured after 1974.

BENEFITS

- Protects system components with anti-wear additives
- Inhibits rust and corrosion
- Economical fluid for aging equipment or frequent fluid replacement
- Three-season protection

APPLICATION

- Construction equipment
- Farm tractors
- Logging equipment such as skidders, feller bunchers, harvesters, loaders

TYPICAL PROPERTIES

METHOD

334

API Gravity	D-4052	28.0
Specific Gravity at 15.6°C	D-4052	0.886
Viscosity, cSt at 100°C	D-445	57.0
Viscosity, cSt at 40°C	D-445	8.9
Flash Point, COC °C (°F)	D-92	218 (425)
Pour Point, °C (°F)	D-97	-30 (-22)
ML Reference No.		566872

NOTE:

The information on this Product Data Sheet is believed to be accurate and is typical of current production. Specifications are subject to change without notice. For additional qualifications, please contact Martin Lubricants Technical Service Department.

Health And Safety Information See separate Safety Data Sheets available on request.

Xtreme™ and Martin Lubricants™ are trademarks of Martin Lubricants. All other marks are property of their respective owners

