



# Dex III/Merc

Automatic Transmission Fluid

Premium Multi-Functional ATF



ATF

REV: 02.20.2020



## DESCRIPTION

Xtreme™ Dex III / Merc ATF is a premium, multi-functional automatic transmission fluid designed to service most General Motors, Ford Motor Company and many Chrysler Corporation vehicles from the early 1980s up to around 2005. This product may be used wherever General Motors Dexron®, Dexron® II, Dexron® IIE, Dexron® III and Ford Mercon is recommended.

Xtreme Dex III / Merc ATF has outstanding low temperature properties, controlled frictional characteristics, outstanding resistance to oxidation and can be used in many industrial applications calling for premium hydraulic oils where long life and superior performance are required.

## BENEFITS

- ❑ Excellent low temperature properties
- ❑ Outstanding oxidation life
- ❑ Protection against corrosion and wear
- ❑ Mixes safely with most OEM fluids
- ❑ Proper frictional control for General Motors, Ford & Chrysler transmissions

## APPLICATION

- Dex III / M - all General Motors vehicles requiring Dexron™, Dexron II™, Dexron™ IIE, Dexron™ III G & H
- D-III / M - all Ford motor company vehicles requiring Mercon™
- D-III / M - all GM Allison heavy duty transmissions where Dexron™ II or Dexron™ III, C-3 or C-4 fluids are recommended

*Note: Not recommended for GM transmissions calling for Dexron™ VI or Ford transmissions calling for Type F, Mercon™ V, Mercon™ SP, or Mercon™ LV*

## PERFORMANCE

### Performance Levels

- General Motors: Dexron™, Dexron™ II, Dexron™ IIE, Dexron™ III, Dexron™ III G, Dexron™ III H
- Ford Motor Company: M - Mercon™
- Caterpillar: TO-2
- Allison: C-3, C-4

TYPICAL PROPERTIES	METHOD	Dex / Merc ATF
Specific Gravity at 15.6°C	D-1298	0.8644
Viscosity, cSt at 40°C	D-445	39.3
Viscosity, cSt at 100°C	D-445	7.5
Low Temperature Pumping, cP	D-2983	15,000 @ -40°C
Viscosity Index	D-2270	161
Flash Point, COC °C (°F)	D-92	226 (439)
Pour Point, °C (°F)	D-97	-51(-60)
Color	Visual	Red
ML Reference No.		567533



### NOTE:

The information on this Product Data Sheet is believed to be accurate and is typical of current production. Specifications are subject to change without notice. For additional qualifications, please contact Martin Technical Service Department.

**Health And Safety Information** See separate Safety Data Sheets available on request.

**Xtreme™ and Martin Lubricants™** are trademarks of Martin Lubricants. All other marks are property of their respective owners